

Energy & Strength All Rolled-up In A WinDow Brand You Can Trust...



The Tilt & Turn WinDow... Certainly Not Invented By WinDoor Incorporated...But Definitely Tweaked And Fine-Tuned To Perfection.

The Perfect WinDow for Residential or Commercial Projects Homes - Condos - Schools - Hospitals - Apartments Governmental Buildings Even the Military.

We Custom Build IT...

High Performance Ratings:

V-100 Series Impact Or Non-Impact Max Size Single 54" x 84" Twin 84" x 80" V-101 & V-102 Series Non-Impact Only Max Size Single 48" x 78" - Twin 84" x 78"

The Vinyl Tilt & Turn WinDow System: Was Awarded The Crystal Achievement Award For... "Most Innovative Window"

This European Style WinDow: Features dual functioning hardware that makes the Tilt & Turn one of our most Smart Choices Available.

Combining modern styling with the ability to provide easy ventilation and cleaning options. The ingenious "Tilt & Turn" hardware allows just the right amount of exhausted ventilation, redirecting air-upward, and eliminating wind gusts while the WinDow is tilted in position.

Colorful Choices: Our Vinyl Products come in White or Bronze, or two tone, Bronze out / White in. Or can be painted Any Color Under The Sun, as well as our woodgrain options. 4 Standard Woodgrain Colors













Golden Oak

Rich Cherry

American Walnut

The colors shown above are as close as possible to the actual colors offered within the limitations of color on paper reproduction. Paint samples are available upon request.



www.WinDoorlnc.com MADE IN AMERICA





The Tilt & Turn WinDows offer the option of being opened in both directions, either tilted

One Hand **Operational Handle System**





You can lock the entire WinDow or by turning the key a half-turn the WinDow system will only Tilt-In.





in vertically or pivoted

horizontally, all from

a single handle.

employs a series of mushroom-cams and striker plates which prevent the sash from being pried out. Featuring SIEGENIA Hardware

Spec Data Sheet Vinyl Tilt & Turn WinDow



High Performance Testing Results:

V-100 Impact or Non-Impact

Single Vent 54" x 80" - Horz Twin 84" x 80" Vert Stacked 54" x 159" - W/ Hy-Vent Hopper 48" x 108" Tested Non-Impact +130 / - 150 psf -Impact +100 / - 130 psf - 20 lbs Water

· V-101 Non-Impact Only Single Vent 48" x 78" - Horz Twin 84' x 78' W/ Hy-Vent Hopper 48" x 108"

+70 / 100 psf - 15 lbs Water

· V-102 Non-Impact Only Integral Fin Single Vent 48" X 78" Horz Twin Vent 84" x 78" W/ Hy-Vent Hopper 48" x 108" +70/-80 psf - 15 Lbs Water

· Whole product NFRC ratings. R-5 Rating U-value as low as .18 Solar Heat Gain Coefficient as Low as .05 STC Rating 41



Screens:

Full Size Screens available



Field Mullions High Design Pressures:

180 degree - Vinyl W Aluminum Reinforcing



Glazing: Standard Argon filled

Non-Impact Insulated 1" Std. Non Impact Triple Glazed 11/2" Std Impact Insulated 1" Std. (Optional 11/4") Impact Triple Glazed 11/2" Std (Optional Glass Configuration Still 11/2" Overall) ** Optional Blinds between glass – Changes glass thickness Will need the 11/4" glass stop. (Minimum air space is 3/4")

Muntins: True Divided Lite Muntin-Maximum Span 54" (Think Window Size) **Internal Muntins - Various Configurations** Between Glass. Applied Muntins - Applied Over Internal Muntins - 1" Wide

Hardware Options:

Standard is Tilt/Turn Handle w/Keylock -White - Bronze or Black custom color **Brass Forgings Optional** (Polished Brass, Oil Rubbed Bronze, Satin Nickel) Optional Custodial E-Plate w/ Handle.



Also Rated for Bomb Blast Protection

A.T.F.P Anti-Terrorism Force Protection GSA Performance Level 1 - No Break 60" x 95 1/2"

WinDow Options - Qualifying multiple individual units with a vertical mull and /or coupling system using the base unit test size of 54" x 80"



